



FASEROPTIK


RFQ-Medizintechnik GmbH & Co. KG

Bruderhofstr. 10 - 12
D-78532 Tuttlingen

Telefax (07461) 9617-20
Telefon (07461) 9617-0

E-Mail: info@rfq.de
<http://www.kaltlichtkabel.de>

COMPARISON LIST FIBER LIGHT GUIDES



KARL STORZ

SYSTEM STANDARD

Fibre Bundle Diameter	Length mm	RfQ-Article Cable	Projector Fitting	Endoscope Fitting	Storz-Article
2,5	1800	on request	00-21110-70	00-21010-71	495 NT
2,5	2300	on request	00-21110-70	00-21010-71	495 NTA
3,5	1800	00-21110-60	00-21110-70	00-21010-71	495 NL
3,5	2300	00-21110-61	00-21110-70	00-21010-71	495 NA
3,5	3000	00-21110-63	00-21110-70	00-21010-71	495 ND
4,9	1800	00-21210-66	00-21110-70	00-21010-71	495 NB
4,9	2500	00-21110-69	00-21110-70	00-21010-71	495 NCS
4,9	3000	00-21210-63	00-21110-70	00-21010-71	495 NE
2,5 LE 90°	1800	on request	00-21110-70	00-21010-71	495 NTW
2,5 LE 90°	2300	on request	00-21110-70	00-21010-71	495 NTX
3,5 LE 90°	1800	00-21310-60	00-21110-70	00-21010-71	495 NW
3,5 LE 90°	2300	00-21310-66	00-21110-70	00-21010-71	495 NWM
3,5 LE 90°	3000	on request	00-21110-70	00-21010-71	495 NWL
3,5 LA 90°	2300	on request	00-21110-70	00-21010-71	495 NV
3,5 LA 90°	3000	on request	00-21110-70	00-21010-71	495 NVL
3,5 (2x LA)	1800	on request	00-21110-70	00-21010-71 (2)	495 DU
3,5 (2x LE)	1800	on request	00-21110-70 (2)	00-21010-71	495 AD
4,9 (2x LE)	1800	on request	00-21110-70 (2)	00-21010-71	495 BD
2,5 DCI	3200	on request	00-21110-70	00-21010-71	495 DV
3,5 DCI	3200	on request	00-21110-70	00-21010-71	495 DC
2,0 FLUID	2200	on request	00-21110-70	00-21010-71	495 FS
3,0 FLUID	1800	on request	00-21110-70	00-21010-71	495 FO
3,0 FLUID	2500	on request	00-21110-70	00-21010-71	495 FP
5,0 FLUID	1800	00-22530-30	inkl	00-21010-71	495 FQ
5,0 FLUID	2500	00-22530-40	inkl	00-21010-71	495 FR
3,5 STIRN	2300	on request	on request	on request	495 NAS
2,5 STIRN	2300	on request	on request	on request	495 NTAS
3,5 STIRN 90°	2300	on request	on request	on request	495 NWMS
2,5 STIRN 90°	2300	on request	on request	on request	495 NTXS

Fiber Light Guides are not 100% like Cables from Original Manufacturer
Errors excepted

LE=LIGHT INPUT LA=LIGHT OUTPUT

HIGH TEMPERATURE FIBER LIGHT GUIDES - PLEASE SEE PAGE 2



FASEROPTIK


RFQ-Medizintechnik GmbH & Co. KG

Bruderhofstr. 10 - 12
D-78532 Tuttlingen

Telefax (07461) 9617-20
Telefon (07461) 9617-0

E-Mail: info@rfq.de
<http://www.kaltlichtkabel.de>

COMPARISON LIST FIBER LIGHT GUIDES



KARL STORZ

SYSTEM FUSED

TO BE USED WITH HIGH TEMPERATURE LIGHT SOURCES

Fibre Bundle Diameter	Length mm	RfQ-Article Cable	Projector Fitting	Endoscope Fitting	Storz-Article
2,5	1800	00-22430-30	00-21110-70	00-21010-71	495 NT
2,5	2300	00-22430-40	00-21110-70	00-21010-71	495 NTA
3,5	1800	00-22330-30	00-21110-70	00-21010-71	495 NL
3,5	2300	00-22330-40	00-21110-70	00-21010-71	495 NA
3,5	3000	00-22330-50	00-21110-70	00-21010-71	495 ND
4,9	1800	00-22230-30	00-21110-70	00-21010-71	495 NB
4,9	2500	00-22230-45	00-21110-70	00-21010-71	495 NCS
4,9	3000	00-22230-50	00-21110-70	00-21010-71	495 NE
2,5 LE 90°	1800	on request	00-21110-70	00-21010-71	495 NTW
2,5 LE 90°	2300	on request	00-21110-70	00-21010-71	495 NTX
3,5 LE 90°	1800	on request	00-21110-70	00-21010-71	495 NW
3,5 LE 90°	2300	on request	00-21110-70	00-21010-71	495 NWM
3,5 LE 90°	3000	on request	00-21110-70	00-21010-71	495 NWL
3,5 LA 90°	2300	on request	00-21110-70	00-21010-71	495 NV
3,5 LA 90°	3000	on request	00-21110-70	00-21010-71	495 NVL
3,5 (2x LA)	1800	00-22230-68	00-21110-70	00-21010-71 (2)	495 DU
3,5 (2x LE)	1800	00-22230-72	00-21110-70 (2)	00-21010-71	495 AD
4,9 (2x LE)	1800	on request	00-21110-70 (2)	00-21010-71	495 BD
2,5 DCI	3200	on request	00-21110-70	00-21010-71	495 DV
3,5 DCI	3200	on request	00-21110-70	00-21010-71	495 DC
2,0 FLUID	2200	on request	00-21110-70	00-21010-71	495 FS
3,0 FLUID	1800	on request	00-21110-70	00-21010-71	495 FO
3,0 FLUID	2500	on request	00-21110-70	00-21010-71	495 FP
5,0 FLUID	1800	00-22530-30	inkl	00-21010-71	495 FQ
5,0 FLUID	2500	00-22530-40	inkl	00-21010-71	495 FR
3,5 STIRN	2300	on request	on request	on request	495 NAS
2,5 STIRN	2300	on request	on request	on request	495 NTAS
3,5 STIRN 90°	2300	on request	on request	on request	495 NWMS
2,5 STIRN 90°	2300	on request	on request	on request	495 NTXS

Fiber Light Guides are not 100% like Cables from Original Manufacturer

Errors excepted

LE=LIGHT INPUT

LA=LIGHT OUTPUT